

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/000713 A1

(51) International Patent Classification⁷: B66B 11/02, 5/00

(21) International Application Number:

PCT/IB2002/002292

(22) International Filing Date: 20 June 2002 (20.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US Not furnished (CIP)
Filed on Not furnished

(71) Applicant (for all designated States except US): OTIS ELEVATOR COMPANY [US/US]; 10 Farm Springs Road, Farmington, CT 06032-2568 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): DET, Franck [FR/FR]; 170, rue du quartier des Champs, F-45500 Saint-Martin-sur-Ocre (FR). DOMINGUEZ, Franck [FR/FR]; 8, allée du bois joli, F-45560 Saint-Denis-En-Val (FR).

(74) Agent: JOLLY, Jean-Pierre; Cabinet Jolly, 54, rue de Clichy, F-75009 Paris (FR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SAFETY TOP BALUSTRADE FOR A CAR OF A MACHINE ROOM-LESS ELEVATOR



(57) Abstract: Safety top balustrade for a car of a machine room-less elevator which moves in a hoistway, on a wall of which the controller of the elevator is secured, said balustrade comprising: - a fixed structure (21) comprising a plurality of vertical uprights (24) fixed at intervals near edge of the car roof (16) and at least two horizontal tubular guard rails (20, 30) fixed at different heights on the uprights, around the periphery of the car roof, except at the place which is in front of the controller (14) when the car is at the level of controller, in order to leave a passage (33) for direct access to the latter, - a mobile structure (34) comprising at least two horizontal bars (36, 38) which are telescopically mounted inside the tubular guard rails, so as to slide between an open position where the bars are inserted within the guard rails, to free said passage towards the controller, and a closed position where the bars are extended out of the guard rails, whereby said passage is obstructed.

SAFETY TOP BALUSTRADE FOR A CAR OF A MACHINE
ROOM-LESS ELEVATOR

FIELD OF THE INVENTION

This invention concerns a safety balustrade mounted on the roof of a car of a machine room-less elevator.

TECHNICAL BACKGROUND

5 In modern elevator installations, the tendency is to reduce as much as possible the ground surface and the height occupied by the installation. One of the solutions found to reach this aim is to eliminate the machine room which, till now, was located either at the top or at the bottom of the hoistway or else in a lateral local of the hoistway, and to
10 secure the control equipment, for instance the controller, on a wall of the hoistway. Nowadays, it is well known to manufacture machines and controllers having a small thickness, which can then be secured in the space comprised between the hoistway and the car.

15 In the elevators of this kind, a balustrade is generally provided on the roof of the car, in a position somewhat offset from the edge of the roof to prevent any risk of falling into the hoistway when the roof is not at the level of the controller.

20 When a technician had to intervene on the controller or on the machine to effect maintenance or reparation operations, he has to climb onto the roof, to control the motion of the car and to stop it when the controller is within easy reach. Since the controller protrudes with respect to the wall of the hoistway, it arrives sufficiently near to the car to eliminate any risk of falling in the hoistway.

25 However, the technician had to work through the bars of the balustrade, or over the balustrade, i.e. at distance from the controller. In this position, certain working operations become rapidly uncomfortable and tiring. Furthermore, since the balustrade must be made of steel to guarantee sufficient resistance, its interposition between the technician and the controller increases the risk of electrical
30 shock during operations made on electrical components.

SUMMARY OF THE INVENTION

5 The object of this invention is to solve these problems. To this end, the invention provides a safety top balustrade for a car of a machine room-less elevator which moves in a hoistway, on a wall of which the controller of the elevator is secured, said balustrade comprising :

10 - a fixed structure comprising a plurality of vertical uprights fixed at intervals near the edge of the car roof, and at least two horizontal tubular guard rails fixed at different heights on the uprights, around the periphery of the car roof, except at the place which is in front of the controller when the car is at the level of the controller, in order to leave a passage for direct access to the latter,

15 - a mobile structure comprising at least two horizontal bars which are telescopically mounted inside the tubular guard rails, so as to slide between an open position where the bars are inserted within the guard rails, to free said passage towards the controller, and a closed position where the bars are extended out of the guard rails, whereby said passage is obstructed.

20 The mobile structure is maintained in its closed position whenever the roof is not at the level of the controller and is brought to its open position only when the car stops at this level. In this position, there is no danger of falling because the controller is in close proximity to the edge of the car roof. However, in order to increase the security of the technician, and to allow him to approach closer to the controller, 25 the roof of the car can be equipped with a bridge, comprised of a simple plate slidingly mounted on the car roof between a retracted position and an extended position in which a part of its length protrudes from the car roof over the space comprised between the car and the wall of the hoistway.

30 In its extended position, the end of the bridge can lie on a support bracket secured to the controller or to the wall of the hoistway.

35 The bars of the mobile structure can be independent and then they must be moved independently from their open position to their closed position and vice versa. In a more advantageous embodiment, the bars are connected at their outer ends by a vertical cross bar so that they can be integrally moved. The cross bar also acts as an

abutting element which limits the movement of the mobile structure in its open position.

5 The mobile structure can be secured in either its retracted and open positions by means of locking elements, such as pins or bolts, which pass through holes drilled in the guard rails and in the bars. The mobile structure is then prevented to slide accidentally.

BRIEF DESCRIPTION OF THE DRAWINGS

10 An embodiment of the invention will be now described with reference to the enclosed drawing in which:

Figure 1 shows a partial perspective view of an elevator car equipped with a balustrade according to the invention, the mobile structure of the balustrade being shown in the extended open position and the bridge in the retracted position ; and

15 Figure 2 is a perspective view similar to Figure 1, and shows the mobile structure in the retracted position and the bridge in the extended position.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

20 The elevator installation 10 shown in the drawings is of the type machine room-less. The controller 14 of the elevator is fixed to a wall 12 of the hoistway in which the car 18 moves.

25 The interventions on the controller are made from the roof 16 of the car 18. The roof is equipped with a balustrade 20 which surrounds the roof, except along the edge of the roof which is adjacent to the front wall of the car, not shown, in which the car door 22 is located. The balustrade is not necessary on this side because the interval between said front wall of the hoistway is very little, and therefore there is no danger of falling.

30 The balustrade 20 comprises a fixed structure 21 comprising a plurality of vertical uprights 24 fixed near the periphery of the roof, and at least two horizontal tubular guard rails 26, 30 fixed at the top and at half-height of the vertical uprights respectively.

35 Each guard rail is U-shaped and comprises three tubes made of steel and having substantially the same lengths as the edges of the roof respectively. The tubes of each guard rail are fixed to each other by

welding, screwing or the like. Said tubes have preferably a square cross section.

In the drawings, there are uprights 24 along the left and right edges of the roof, but not along the rear edge, and the tubes of the guard rails extending along said rear edge are connected therebetween by a strut 32. Of course, uprights can also be mounted on the rear edge of the roof.

Preferably, the upper guard rail 26 is fixed on the uprights at waist height.

According to the invention, the fixed structure 21 is interrupted on its right side in Figure 1, at the place which having a width is in front of the controller 14, thereby leaving a free passage 33 having a width which corresponds substantially to the width of the controller. This passage can be closed by a mobile structure 34 comprising at least two bars 36, 38 which are telescopically inserted within the ends of the tubular guard rails 26, 30. The bars 36, 38 are made of steel and have a square cross section. They are connected to each other at their ends by a vertical cross bar 40 whereby they can slide integrally. Said cross bar acts also as an abutting element which stops the mobile structure when it is completely open.

According to an advantageous embodiment of the invention, a foot-bridge 42 is slidably mounted on the roof of the car, along guides 44 extending in a direction transversal to the passage 33.

Figure 1 shows the normal position of the balustrade in which the technician finds it when he climbs onto the roof : the mobile structure 34 is extended and obstructs the passage 33, while the bridge 42 is retracted and lies completely on the roof 16. After the technician has moved the car until the level of the controller, he drives the mobile structure 34 leftward on Figure 1 to free the passage 33, and then he draws the bridge 42 out of the roof. The presence of the bridge prevents small objects, such as screws and bolts, from falling in the hoistway.

Increased stability can be provided for the portion of the bridge which protrudes from the roof if its end lies on a support bracket, not illustrated, fixed to the hoistway or on the controller.

The mobile structure 34 can be secured in its retracted position or in its extended position, by means of pins or bolts 46 inserted through holes drilled in the guard rails 26, 30 and in the bars 36, 38.

CLAIMS

1. Safety top balustrade for a car of a machine room-less elevator which moves in a hoistway, on a wall of which the controller of the elevator is secured, said balustrade comprising :

- a fixed structure (21) comprising a plurality of vertical uprights (24) fixed at intervals near the edge of the car roof (16) and at least two horizontal tubular guard rails (20, 30) fixed at different heights on the uprights, around the periphery of the car roof, except at the place which is in front of the controller (14) when the car is at the level of the controller, in order to leave a passage (33) for direct access to the latter,
- a mobile structure (34) comprising at least two horizontal bars (36, 38) which are telescopically mounted inside the tubular guard rails, so as to slide between an open position where the bars are inserted within the guard rails, to free said passage towards the controller, and a closed position where the bars are extended out of the guard rails, whereby said passage is obstructed.

2. Balustrade according to claim 1, characterized in that a bridge (42) comprising a horizontal plate is slidably mounted on the roof (16) of the car between a retracted position in which it is placed completely on the roof, and an extended position in which a portion of the bridge protrudes outside of the roof across the space between the car (18) and the wall (12) of the hoistway on which the controller is fixed.

3. Balustrade according to claim 2, characterized in that when the bridge is extended, its end lies on a support bracket fixed to the controller, or to the wall of the hoistway on which the controller is fixed.

4. Balustrade according to claim 1, characterized in that the bars (36, 38) of the mobile structure are connected at their ends by a vertical cross bar (40) which acts as an abutting element and which allows the mobile structure to be moved integrally.

5. Balustrade according to claim 1, characterized in that the mobile structure (34) is secured in its retracted position or in its extended position by means of locking elements (46), such as pins or bolts (46) inserted through holes drilled in the guard rails and the bars.

6. Balustrade according to one of the preceding claims, characterized in that the guard rails (26, 30) and the bars (36, 38) have a square section and are made of steel.



INTERNATIONAL SEARCH REPORT

In **Optional Application No**
PCT/IB 02/02292

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B66B11/02 B66B5/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B66B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 985 628 A (TOKYO SHIBAURA ELECTRIC CO) 15 March 2000 (2000-03-15) abstract; figures	1
A	--- PATENT ABSTRACTS OF JAPAN vol. 2002, no. 09, 4 September 2002 (2002-09-04) & JP 2002 128433 A (MITSUBISHI ELECTRIC CORP), 9 May 2002 (2002-05-09) abstract	2
A	--- PATENT ABSTRACTS OF JAPAN vol. 2002, no. 04, 4 August 2002 (2002-08-04) -& JP 2001 341950 A (MITSUBISHI ELECTRIC CORP), 11 December 2001 (2001-12-11) abstract; figures -----	2

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

- 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- 'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- 'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- '&' document member of the same patent family

Date of the actual completion of the international search

4 March 2003

Date of mailing of the international search report

11/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Salvador, D

INTERNATIONAL SEARCH REPORT
Information on patent family members

In ternational Application No
PCT/IB 02/02292

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0985628	A	15-03-2000	JP 2000143125 A CN 1246437 A EP 0985628 A2 KR 2000022841 A TW 446680 B	23-05-2000 08-03-2000 15-03-2000 25-04-2000 21-07-2001
JP 2002128433	A	09-05-2002	NONE	
JP 2001341950	A	11-12-2001	NONE	